



Optimized for Smooth VoIP and Data Exchange

- **Compact, sturdy desktop switch with alternative wall-mount installation**
- **Connect up to 5/8 network devices at Gigabit wire speed**
- **QoS ports for optimized, smooth VoIP and data transfer of high- and medium-priority applications**
- **Green switch for energy saving**
- **Loop detection prevents network from crashing**

The ZyXEL GS-105B v3/GS-108B v3 5/8-Port Desktop Gigabit Ethernet Switch connects network devices and the home network at blazing Gigabit speed. The newly designed QoS ports guarantee smooth transfer for bandwidth-intensive applications such as VoIP and data communications.

Benefits

Compact, sturdy switch with alternative wall-mount design

The GS-105B v3/GS-108B v3 fits any environment. Regardless of desktop or wall-mount installation, its sturdy, compact design provides more flexibility for wired home networks.

Fast, reliable wired connectivity

Without any manual configuration, the GS-105B v3/GS-108B v3 can boost data transfer speed for connected network devices such as IP phones, network storages, PCs and laptops to the network at blazing-fast Gigabit speed.

Optimized for smooth VoIP and data exchange

The GS-105B v3/GS-108B v3 has 3/4 QoS ports with an assigned high- and medium-priority mechanism to enhance the stability of VoIP and data exchange. Just connect network devices such as IP phones, PCs, laptops or network storages to the high-priority or medium-priority ports of your choice, you can then enjoy smooth VoIP communication and data transfer at the same time.

**GS-105B v3
GS-108B v3
5/8-Port Desktop Gigabit
Ethernet Switch**



Detect
Cable Length



Adjust
Power Usage



Green switch saves energy

Compliant with the IEEE 802.3az Energy Efficient Ethernet standard, the GS-105B v3/GS-108B v3 provides power-saving benefits without compromising performance. The GS-105B v3/GS-108B v3 can automatically adjust power consumption according to the number of active, connected network devices and cable length; that is, it consumes less power if fewer network devices are connected and active, or when the length of Ethernet cable is shorter.

Specifications

System Specifications

Standard

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- IEEE 802.3 Nway auto-negotiation
- IEEE 802.3x full duplex operation and flow control
- IEEE 802.3az Energy Efficient Ethernet

Performance

- Data transfer rate (half duplex/full duplex):
 - Ethernet: 10/20 Mbps
 - Fast Ethernet: 100/200 Mbps
 - Gigabit Ethernet: 1000/2000 Mbps
- MAC address table:
 - GS-105B v3: 2 K
 - GS-108B v3: 8 K
- Memory buffer:
 - GS-105B v3: 128 KB
 - GS-108B v3: 128 KB
- Switching fabric (non-blocking):
 - GS-105B v3: 10 Gbps
 - GS-108B v3: 16 Gbps

Features

- Auto-MDI/MDIX in all ports
- Transmission method:
 - Store-and-forward architecture
- Loop detection support
- Port-based QoS support
- Jumbo frame support up to 9 KB

Hardware Specifications

Interface

- GS-105B v3: Five RJ-45 10/100/1000 Mbps Ethernet ports with auto MDI/MDIX support
- GS-108B v3: Eight RJ-45 10/100/1000 Mbps Ethernet ports with auto MDI/MDIX support

QoS Ports

- GS-105B v3: One high-priority QoS port and two medium-priority QoS ports
- GS-108B v3: Two high-priority QoS ports and two medium-priority QoS ports

LED Indicator

- PWR: Power
- Per port: Link/Activity
 - Amber: 10/100 Mbps
 - Green: 1000 Mbps

Power Supply

- GS-105B v3:
 - Input: 100 - 240 V AC
 - Output: 5 V DC, 1 A
- GS-108B v3:
 - Input: 100-240 V AC
 - Output: 5 V DC, 1 A

Power Consumption

- GS-105B v3: 2.5 watt max.
- GS-108B v3: 3.0 watt max.

Physical Specifications

- Item dimensions (WxDxH):
 - GS-105B v3: 121 x 75 x 26 mm (4.8" x 3.0" x 1.0")
 - GS-108B v3: 155 x 85 x 26 mm (6.1" x 3.3" x 1.0")
- Item weight:
 - GS-105B v3: 229 g (0.50 lb.)
 - GS-108B v3: 325 g (0.72 lb.)
- Packing dimensions (WxDxH):
 - GS-105B v3: 127 x 82 x 95 mm (5.0" x 3.2" x 3.7")
 - GS-108B v3: 161 x 90 x 95 mm (6.3" x 3.5" x 3.7")
- Packing weight:
 - GS-105B v3: 381 g (0.84 lb.)
 - GS-108B v3: 493 g (1.09 lb.)

Environmental Specifications

Operating Environment

- Temperature: 0°C to 50°C (32°F to 122°F)
- Humidity: 10% to 90% (Non-condensing)

Storage Environment

- Temperature: -40°C to 70°C (-40°F to 158°F)
- Humidity: 10% to 95% (Non-condensing)

Certification


- CE, FCC Class B, BSMI

Package Contents


- Gigabit switch
- Power adapter
- Quick start guide

Application Diagram

GS-105B v3



GS-108B v3



For more product information, visit us on the web at www.ZyXEL.com



Copyright © 2015 ZyXEL Communications Corp. All rights reserved. ZyXEL, ZyXEL logo are registered trademarks of ZyXEL Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

